

# High-Density Low-Emission Gasket



## Advanced Sealing

### DESCRIPTION

The High-Density, Low-Emission (HDLE) spiral wound gasket is built to a higher standard so that it seals to a lower level of emission control. With more metal windings per inch and graphite that is both denser and wider, this gasket has been shown to seal 100 times tighter than standard spiral wound gaskets. The high-density construction limits compression of the winding, ensuring that the gasket load remains on the sealing element rather than the centering rings. Wherever you have light-end, volatile gases to seal, the HDLE spiral wound is your proven champion.

### APPLICATION

Manufactured in full compliance with ASME B16.20, the HDLE spiral wound gasket is entirely interchangeable with standard spiral wounds. HDLE gaskets are designed to minimize fugitive emissions in bolted joint connections. Wherever you have light-end, volatile gases to seal, the HDLE spiral wound is your proven champion.

### SEALING CHARACTERISTICS

- With improved sealability, the HDLE gasket provides up to 100 times better sealing than standard SWG.
- The HDLE gasket is considered an emission control device to actively reduce VOC emissions.
- Due to gasket design, the HDLE seals at lower seating stresses than standard SWG.
- The HDLE uses APX2 flexible graphite filler material with extremely low oxidation rates at elevated temperatures, making it suitable for services up to 1,000°F.

### CHEMICAL COMPATIBILITY

Subject to materials, the HDLE gasket can be used in a wide variety of media, with a pH range varying from 0 to 14. Our Application and Compatibility Guide is available upon request.

### AVAILABLE OPTIONS

HDLE gaskets are manufactured per ASME B16.20 and are readily available in sizes from ½" to 24" NPS. Custom sizes are available upon request.

### APPROVALS & CERTIFICATES

- ASME B16.20
- It is well established in the industry that APX2 is a fire-rated material, along with any gasket incorporating it as a component. For additional information, please consult the Engineering team.

Technical Data & Sealing Characteristics	
Maximum Temperature	1,000°F
Maximum Pressure	150 – 2500 psi M Value = 3
Minimum Full Width Gasket Stress	5,000 psi
Minimum Recommended Gasket Stress	10,000 psi
Maximum Recommended Gasket Stress	40,000 psi

All information contained on this datasheet is subject to change without prior notice. LGG INDUSTRIAL, INC. AND ITS AFFILIATES MAKE NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance, and storage of gaskets and other sealing products may result in the product's failure to perform properly and may result in damage to property and/or serious injury. LGG Industrial, Inc. and its affiliates shall not be subject to, and they hereby disclaim, any obligations or liabilities (including but not limited to all consequential, incidental, and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.