

ALKY-ONE® Gasket



DESCRIPTION

To meet the challenges of sealing Hydrofluoric Acid, our patented, fire-safe ALKY-ONE® gasket uses a Monel 400 Kamprofile primary seal and a 100% expanded PTFE barrier pillow to provide ID-to-OD sealing. The ALKY-ONE® gasket has a carbon steel outer ring. However, other alloys are available upon request.

APPLICATION

The ALKY-ONE® gasket is available for Hydrofluoric Alkylation Units and Sulfuric Alkylation Units. The ALKY-ONE® gasket is used for service temperatures up to 500°F.

SEALING CHARACTERISTICS

- This gasket's unique, patented features ensure that it will seal more quickly and tightly than any other alky-service gasket.
- The unique, integrally attached Barrier Pillow, made from 100% expanded PTFE, prevents acid intrusion and pooling on flange faces, reducing or eliminating the need to replace eroded flanges.

CHEMICAL COMPATIBILITY

The ALKY-ONE® gasket utilizes materials specifically selected to provide chemical resistance for the intended service application.

AVAILABLE OPTIONS

For Hydrofluoric Acid Applications: Monel 400 core, standard; carbon steel core, optional. For Sulfuric Acid Applications: 316 Stainless Steel, standard. Available for ASME B16.5 and ASME B16.47 flanges.

APPROVALS & CERTIFICATES

- Fire-safe certified per API 607

Technical Data & Sealing Characteristics	
Maximum Temperature	500°F
Maximum Pressure	Suitable for 150 and 300 pressure class flanges. For use in pressure classes above 300, consult with the Engineering team.
Minimum Recommended Gasket Stress	5,000 psi
Maximum Recommended Gasket Stress	40,000 psi

All information contained on this datasheet is subject to change without prior notice. LGG INDUSTRIAL, INC. AND ITS AFFILIATES MAKE NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. Buyer/end-user is responsible for determining whether the product is fit for a particular purpose and suitable for buyer's/user's method of use or application. Failure to follow procedures for selection, installation, care, maintenance, and storage of gaskets and other sealing products may result in the product's failure to perform properly and may result in damage to property and/or serious injury. LGG Industrial, Inc. and its affiliates shall not be subject to, and they hereby disclaim, any obligations or liabilities (including but not limited to all consequential, incidental, and contingent damages) arising from tort claims (including without limitation negligence and strict liability) or other theories of law.